



## DOUBLE 4K SENSOR | NDVI + NDRE



Sentera's Double 4K Sensor with NDVI and NDRE data capture helps agronomists, crop consultants and growers easily gain plant health insights so they can take action on or off the field.

Featuring innovative filtering, you can simultaneously collect normalized difference vegetation index (NDVI) and normalized difference red edge (NDRE) data - critical plant health indices that offer a vegetative health report card, more complete than ever before.

Sentera's Double 4K sensor delivers crop health insights at an unmatched 4K resolution, allowing you to confidently leverage scouting results to perform analysis and help take action.

### FEATURES & BENEFITS

- Simultaneously collects 12MP NDVI and NDRE data
- Small form factor, fits a GoPro® HERO4 footprint
- Compatible with several drone platforms
- Quickly attaches to DJI Inspire 1 or Inspire 2 drones with easy plug-and-play gimbal technology
- Seamlessly integrates with AgVault™ Web, Mobile, and Desktop software

# DOUBLE 4K SENSOR | NDVI + NDRE

## INSTALLATION OPTIONS

The Sentera Double 4K NDVI + NDRE sensor variant can be integrated on multiple platforms including the Sentera Omni™, DJI Phantom 4, and Lockheed Martin Indago quadrotor drones or a PHX™ fixed-wing drone.

Additionally, the Sentera plug-and-play gimbal allows you to simply click the Double 4K into a DJI Inspire 1 or 2, Matrice 100, 200, or 600 drone. The gimbal stabilizes the sensor and has a dedicated GPS for geo-tagging data. Without tools or modifications, you can quickly swap between the Double 4K sensor and other gimbals, including the X3, XT, and X5.



Plug-and-Play Gimbaled  
Double 4K Sensor on DJI Inspire 1



Double 4K Sensor on DJI Phantom 4



Double 4K Sensor on Sentera Omni



Plug-and-Play Gimbaled  
Double 4K Sensor on DJI Inspire 2



Double 4K Sensor on Sentera PHX



Double 4K Sensor on  
Lockheed Martin Indago

## SPECIFICATIONS

<b>Sensors</b>	12.3MP BSI CMOS <ul style="list-style-type: none"><li>• Sony Exmor R™ IMX377 Sensor</li></ul>	<b>Data capture</b>	12.3MP Stills 4K Ultra HD video @ 30fps 1080p/720p Video <ul style="list-style-type: none"><li>• H.264 encoding</li></ul>
<b>Spectral bands</b>	NDVI <ul style="list-style-type: none"><li>• Red: 625nm x 100nm width</li><li>• NIR: 850nm x 40nm width</li></ul> NDRE <ul style="list-style-type: none"><li>• Red Edge: 720nm x 40nm width</li><li>• NIR 840nm x 20nm width</li></ul>	<b>Interfaces</b>	Ethernet, Serial/UART, USB 3.0, I2C, GPIO <ul style="list-style-type: none"><li>• Web-based camera configuration</li><li>• Pushbutton control for single photo and mode select</li></ul>
<b>Size</b>	2.32" x 1.61" x 1.75" (59mm x 41mm x 44.5mm) <ul style="list-style-type: none"><li>• Fits the GoPro® Hero4 footprint</li></ul>	<b>Control</b>	Open ICD for triggering and metadata logging over serial or IP, compatible with: <ul style="list-style-type: none"><li>• Lockheed Martin Kestrel™ autopilot</li><li>• PIXHAWK™ autopilot</li><li>• MAVLink™-based systems</li><li>• Customized ICD options available</li></ul>
<b>Weight</b>	80 grams	<b>Storage</b>	64GB SD card, standard and removable
<b>Power</b>	8W typical / 12W maximum	<b>Data integration</b>	Seamlessly integrates with Sentera AgVault™ Web, Mobile, and Desktop Software
<b>Image format</b>	JPEG, TIFF, RAW		
<b>Field of view</b>	60° HFOV (4K Stills / Video) 1080p ranges 30° - 60° HFOV		



### Contact us—let's do something amazing!

Sentera, LLC  
6636 Cedar Ave South, Ste 250  
Minneapolis, MN 55423

+1 (844) SENTERA (844.736.8372)  
+1 (612) 204.2000 direct

www.sentera.com  
info@sentera.com